

Book

Clean, even surface
Several bulk options and good stiffness
Wide range of choices in terms of
grammage, brightness and shades

Customer advantages

Holmen Book is easy on the eye, but then the paper was especially developed to make reading even more of a pleasure. That is why the surface is clean and even. With its high bulk and stiffness, the paper also conveys a sense of quality and stability to the reader.

Opportunities

Holmen Book gives you freedom of choice. The paper is adapted for book printing in both heatset and coldset, and then there is the fact that you can choose from several grammages, levels of brightness and shades. Why not try cream?

Technical target values – Holmen Book White

| | | | | | | | | | | |
|-----------------------|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|
| Bulk | 1,6 | 1,6 | 1,6 | 1,8 | 1,8 | 1,8 | 2,0 | 2,0 | 2,0 | 2,3 |
| Basis weight | 52 | 55 | 60 | 52 | 55 | 60 | 55 | 60 | 70 | 52 |
| ISO Brightness | 75 | 75 | 75 | 72 | 72 | 72 | 75 | 75 | 75 | 58 |
| Caliper µm | 83 | 88 | 96 | 94 | 99 | 108 | 110 | 120 | 140 | 120 |
| Opacity % | 94 | 95 | 96 | 94 | 95 | 96 | 95 | 96 | 97 | 94 |

Technical target values – Holmen Book Cream

| | | | | | | | | | | | | |
|-----------------------|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|
| Bulk | 1,6 | 1,6 | 1,6 | 1,8 | 1,8 | 1,8 | 1,8 | 2,0 | 2,0 | 2,0 | 2,0 | 2,0 |
| Basis weight | 52 | 70 | 80* | 55* | 60 | 70 | 80* | 52 | 55 | 60 | 70 | 80* |
| ISO Brightness | 75 | 75 | 75 | 75 | 75 | 75 | 75 | 75 | 75 | 75 | 75 | 75 |
| Caliper µm | 83 | 112 | 128 | 99 | 108 | 126 | 144 | 104 | 110 | 120 | 140 | 160 |
| Opacity % | 91 | 93 | 95 | 91 | 91 | 93 | 95 | 91 | 91 | 92 | 93 | 94 |

Printing methods: Heatset and Coldset

Updated 2011-08-17

* Subject to trim

Paper Machine Data

Hallsta

| | |
|-----------------|---------------------------|
| Machine | PM 12 |
| Trim | 8.50 m |
| Max reel width | 2750 mm |
| Min reel width | 298 mm |
| Max reel weight | 8 000 kg |
| Standard diam | 1000, 1150, 1200, 1250 mm |
| Core size | 76 mm |

Environment

Renewable resources
 ISO 14001
 FSC
 PEFC